



MPVU750M

MODULAR POWER SUPPLY

SPECIFICATIONS

Power	750W
AC input	200-240V 50-60Hz
PFC	Active
Efficiency	+87%
Noise	14dB
Form Factor	ATX
Fan	140mm
Rail	Single 12V
Certificate	ATX12V, CE, ROHS, TUV
Protections	OCP/OVP/OPP/OTP/OLP/NLO/PFP/UVF/SCP/TCP
Cable type	Full modular
Cables	1x 24 pin, 1x 12V 4+4 pin, 6x SATA, 3x MOLEX, 4x 6+2 pin PCI-E
Dimensions	150x160x85mm / 1.7Kg
Extra	AI-RPM fan control and extra long flat cables

750W ATX fully modular power supply with 80PLUS Silver certification, +87% efficiency. 10 years warranty.

SMD technology with A-Grade components and 105°C Japanese capacitors. Single 12V rail and AI-RPM for an optimized temperature control



AC Input	200-240V		6.5A	50/60Hz	
DC Output Voltage	+3.3V	+5V	+12V	-12V	+5Vsb
Max. Output Current	20A	20A	59A	0.3A	2.5A
Combined Power	130W		708W	3.6W	12.5W
Total Power	750W				

REFERENCE MPVU750M

EAN 8435693104308

UNITS/BOX 8

PACKAGING 206x136x258mm

LOGISTICS